



MPO CASSETTE MODULE

2ELLO's fiber optic modules are developed to cater the chassis range of fiber cable management. The robust steel construction of the modules allows an integration of various fan-out kits (see separate data sheets), such as MPO, SC-simplex and -duplex, E2000, LC-simplex, -duplex and -quad, by granting convenient cable accessibility, bending radius preservation and physical protection, in order to achieve a permanently perfect system performance. Availability ranges from module only, to partially or fully equipped versions. Standard color black (customized colors and logo- prints are available on request).



MPO Cassette Module		
CODICE	DESCRIZIONE	COLORE
8860201-12	Modulo MPO-LC 12 fibre Singlemode 09/125 um OS2	Nero
8860202-12	Modulo MPO-LC 12 fibre Multimode 50/125 um OM2	Nero
8860203-12	Modulo MPO-LC 12 fibre Multimode 50/125 um OM3	Nero
8860204-12	Modulo MPO-LC 12 fibre Multimode 50/125 um OM4	Nero
8860205-24	Modulo MPO-LC 24 fibre Singlemode 09/125 um OS2	Nero
8860206-24	Modulo MPO-LC 24 fibre Multimode 50/125 um OM2	Nero
8860207-24	Modulo MPO-LC 24 fibre Multimode 50/125 um OM3	Nero
8860208-24	Modulo MPO-LC 24 fibre Multimode 50/125 um OM4	Nero

MPO cassette module

Specification

Module	Standard module kit for SC, LC, E2000 or MPO fan out kits
Adapters	SC (simplex e duplex), LC (simplex, duplex e quad), E2000 (simplex e duplex), MPO
Capacity	Up to 24-fibers
Type	Sliding mechanism
Integration	Horizontal or vential (depending on chasis size)
Fixation at chassis/panel	Snap-in
Material of module	Sheet steel
Thickness	1.2mm
Dimensions	H=30mm, D=160mm (box only)/130mm (incl. mounting ears)
Weight	0,5kg (nominal)
Cable entry	Open rear
Strain relief	Cable ties
Standard colors	Black RAL9005 (other colors available on request)

Garanzia di prodotto

Le soluzioni 2ELLO sono coperti dalla garanzia 36 mesi per i difetti di conformità ai sensi dal DLgs n. 24/02.

La garanzia di Sistema permette l'estensione fino a 30 anni nel caso la soluzione venga posata in un impianto con tutti i prodotti passivi a marchio 2ELLO da installatori certificati 2ELLO.

Le soluzioni 2ELLO rispettano la direttiva europea RoHS 2002/95/EC relativa al contenuto di sostanze pericolose. (Restriction of the Use of Certain Hazardous Substance in Electrical and Electronic Equipment.)

